











MODEL S4b



Great for use in 2.1 systems or any channel of theater system utilizing suboofers. Can be used as surround, height or LCR. Bookshelf, stand or on-wall mounting with keyhole or available bracket. Featuring our DPC-Array as for controlling Mid/High frequencies, centered by our finest 28mm Beryllium dome and dual 28mm TPCD ultra-lightweight domes. This new tweeter/waveguide DPC-Array delivers amazing accuracy, smoothness, and directivity control to handle the critical vocal range and delicate treble. The S4b shares the same DPC-Array and benefits from our unique timbre matching technique as found in the entire S-Series range of speakers. Unparalleled dynamic range, low distortion and musical finesse. The Perlisten S4b continues the lineup of speakers that have the distinguished honor to be the world's first and only loudspeakers to be certified for THX Dominus - their highest rating.

TECHNICALSPECIFICATIONS





BASIC

Dimensions (HxWxD) 420 x 240 x 300mm 16.5 x 9.5 x 11.8" **Weight** 11.0 kg (24.2 lbs.)

Available finishesPiano Gloss Black, White
Special Edition Veneers

TECHNICAL

Enclosure Alignment

3-way acoustic suspension

Driver complement

DCP-Array: 28mm Beryllium 28mm(2) Textreme TPCD Woofers: 180mm Textreme TPCD

Sensitivity

85.4dB / 2.83v / 1.0m

Impedance

 4Ω nominal / 3.2Ω min

Response Linearity

100 - 20kHz +/-1.5dB window

Frequency Response (-10dB)

36 - 37kHz

Typical In Room bass extension

30Hz

Recommended Amplifier Power

50 - 300W RMS

SPL capability @1m (100-20kHz)

110.2dB peak

109.0dB peak <3% - 2nd, 3rd Harmonics

Certification

THX Dominus, THX Ultra







TPCD
Thin Ply Carbon Diaphragms

